



PRODUCT SPECIFICATIONS

Controls	Remote, Local or Automated
Variable Flow Water Usage	5 - 80 gpm / 1.2 - 18 m ³ /h
Projection	up to 300 ft 95m
Misting Coverage	260 000 sq. ft 24 200 cubic meters
Height of Gun on Tower	10 to 30 ft 3 to 10m
Oscillation	330 °
Voltage	460 V 600 V 380 V
Frequency	50 Hz / 60 Hz
Fan	25 HP 19 kW
Pump	25 HP 19 kW 70 gpm @ 380 PSI / 15.9 m3/h @ 26 BAR
Camlock Water Connection	1.5 in. or 2 in. (with swivel coupling)
Nozzle	V-Flow Central Nozzle Outer Misting Ring
Warranty	1 year



V-500 FX

The V-Flow 500 FX is designed for fixed dust emissions locations such as dry bulk storage areas and loading terminals, recycling yards, or aggregate facilities. Available on a 20' tower, the V-Flow 500 FX can achieve more than 250' of distance with all the benefits of our Variable Flow central nozzle and remote control functionality. When multiple units are required for complete coverage, the V-Flow 500 FX's can be completely automated with centralized computer control.



HKD Blue
15 Mercer Road
Natick, MA
01760
617-913-7679
gsantry@hkdblue.com



HKD Blue
5780 Boulevard Sainte-Anne
Boischatel, Quebec Canada
GOA 1H0
(800) 613-4546
cgrenier@hkdblue.com